

Batteries

MASTERVOLT

AGM

- Ideal universal battery
- Excellent starter function
- Glass fibre technology ensures low internal resistance
- Perfect upgrade for wet lead acid batteries
- 100% sealed maintenance free
- 2 year manufacturer warranty
- Threaded insert M* stud; standard supplied with easy to mount adaptive round battery terminals
- Cold cranking @ 0°F (-18°C)
- Operating temperature -4°F(-20°C) to 131°F(55°C)



AGM SERIES

Item Number	CCA DIN/SAE	Battery Size	Dimensions in " (mm) LxWxH (w/terminals)	Capacity C20	Price
C20=battery capacity at a discharge time of 20 hours, till 1.75V per cell, dimensions include terminals					
62000900	360/570	Group 31	13(330) x 6.8(173) x 8.7(220)	90 Ah	\$440.22
62001300	590/940	—	16.1(409) x 6.9(175) x 9(228)	130 Ah	\$598.18
62001600	550/870	4D	19.1(485) x 6.7(170) x 9.5(241)	160 Ah	\$702.72
62002250	680/1080	4D	20.6(523) x 9.4(246) x 8.8(223)	225 Ah	\$945.46
62002700	750/1200	Super 8D	20.6(523) x 10.6(269) x 8.9(226)	270 Ah	\$1,120.86

MVG Gel Series

- Perfect service battery for medium and large 12V and 24V systems
- Extremely long lifespan
- No gas formation with normal use
- Fast recharge, high charge current possible
- For intensive cycle use with high number of charge/discharge cycles
- Very low self discharge
- High return on investment



MVG GEL SERIES

Item Number	Cold Cranking Amps DIN/SAE	Dimensions in " (mm) LxWxH (w/terminals)	Capacity C20	Price
64002000	630/1100	20.4(518) x 10.8(274) x 9.4(238)	200 Ah	\$1,295.65

Slimline

- Ideal universal and starter battery
- Compressed AGM technology
- Saves up to 15% in volume and weight
- 2x 185 Ah for a 200 Ah battery footprint
- 2 year manufacturer warranty



AGM-SL 12/185

Item Number	Cold Cranking Amps DIN/SAE	Dimensions in " (mm) LxWxH (w/terminals)	Capacity C20	Price
63001851	580/930	22(559) x 5(127) x 11(279)	200 Ah	\$957.58

List pricing in catalog is subject to change without notice.

Mastervolt

MLI Lithium Ion Series —

CZone®/ MasterBus Compatible

- Top performance, heavy duty Lithium Ion batteries.
- Ideal for running heavy loads for long periods and short charge times.
- Saves up to 70 % in space and weight.
- Three times the lifespan of traditional batteries.
- High cycle efficiency.
- Fast charging up to half an hour.
- High discharge rate up to 3C.
- MasterBus/CAN communication with every Mastervolt battery charger.
- Integrated Battery Management System (BMS).
- Integrated battery monitoring (Ah consumed, state of charge).
- Series connection up to 10 batteries possible.
- Waterproof electronics cabinet.
- Extremely safe LiFePO4 chemistry.
- Tested and certified according to UN38.3.



LITHIUM ION

Item Number	Nominal Voltage	Max. outer dimensions, xwxh (incl. terminals/grip handles)	Price
66011250	12	12.9" x 6.7" x 9.3" 327 x 171 x 235 mm	Call for pricing
66021250	24	12.9" x 6.7" x 9.3" 327 x 171 x 235 mm	Call for pricing
66025500	12	24.5" x 7.8" x 14" 622 x 197 x 355 mm	Call for pricing
66015500	24	24.5" x 7.8" x 14.0" 622 x 197 x 355 mm	Call for pricing